

Part No.	Picture	Matched Linear Light Housing	Product Description	Unit Price
FL-2835W144NR-S		All slim LED Profiles	Working Voltage: 33-42V DC Power: 20-28W Current: 500-700mA Lumen: 2800-3500lm CRI: 80+ Dimension: 1195*12mm or 1195*10mm Cuttable every 10cm	
FL-2835W72NR		ALP5035 ALP3875 ALP5075 ALP5075-C ALP7575 ALP6535 ALP6545-C ALP6875 ALP9575	Working Voltage: 33-42V DC Power: 14-15W Current: 360mA Lumen: 1980lm CRI: 80+ Dimension: 592*26mm	
FL-2835W144NR		ALP7535 ALP10075 ALP9035 ALP12575	Working Voltage: 33-42V DC Power: 20-28W Current: 500-700mA Lumen: 2800-3500lm CRI: 80+ Dimension: 600*62mm	
FL-2835W192NR		ALP12335	Working Voltage: 33-42V DC Power: 30-38W Current: 800-960mA Lumen: 4000-4600lm CRI: 80+ Dimension: 600*74mm	
20W Constant Current LED Driver			Input Voltage: 100-240V AC Output Voltage: 27-42V DC Current: Constant current 500mA PF ≥0.9 Efficiency: 88% Dimension: L195*W30*H21.5	
40W Constant Current LED Driver			Input Voltage: 100-240V AC Output Voltage: 27-42V DC Current: Constant current 750-1000mA PF ≥0.9 Efficiency: 88% Dimension: L245*W30*H21.5	
60W Constant Current LED Driver			Input Voltage: 100-240V AC Output Voltage: 27-42V DC Current: Constant current 1200-1500mA PF ≥0.9 Efficiency: 88% Dimension: L285*W30*H21.5	

80W Constant Current LED Driver			Input Voltage: 100-240V AC Output Voltage: 27-42V DC Current: Constant current 1800-2000mA PF $\geq$0.9 Efficiency: 88% Dimension: L355*W30*H21.5	
--	---	--	---	--